

Cisco TelePresence MX300 G2 and MX200 G2

Product Overview

From box to video in 10 minutes. It doesn't get much easier. You can bring customers, colleagues, and business partners from around the world to work together face-to-face in just about any room or space and at a moment's notice. The Cisco TelePresence® MX300 G2 (MX300 G2) and MX200 G2 (MX200 G2) make it easy to put high-definition video collaboration within reach for everyone at your organization. They deliver ready-to-use simplicity and high quality performance at value pricing so you can make decisions faster and be more productive and innovative. The systems now support cloud registration to [Cisco Spark Services](#) for even faster and more cost effective deployment¹.

The MX300 G2 and MX200 G2 are value products within the MX Series of collaboration room endpoints. They feature a sleek, streamlined industrial design that blends aesthetics, functionality and ease of use at a great value (Figure 1). New features such as dual display and an embedded four-way MultiSite conferencing option deliver more power and flexibility. The Cisco TelePresence Touch 10 user interface offers a larger screen size and a user-friendly experience. Rich 1080p60 high-definition (HD) video and a high-end speaker system optimized for voice encourage people to interact as naturally as if they were in the same room. It's a great way to enable your extended teams to work together whenever and wherever they want.

Figure 1. Cisco TelePresence MX300 G2 and MX200 G2



Cisco MX300 G2 and MX200 G2 systems are as easy to install as a television, and can be set up in about 10 minutes. They're priced for large-scale deployment, so you can quickly and easily transform any meeting space into a video-enabled team room. The MX300 G2 with a 55-inch screen is ideal for medium size rooms. The MX200 G2 has a 42-inch screen that makes it ideal for small-to-medium rooms as it has a wide field of view for tight spaces. Both products are easy to use and affordable enough to make video collaboration possible throughout your organization.

Figure 2. Cisco TelePresence MX300 G2 on Floor Stand



The Cisco TelePresence MX300 G2 and MX200 G2 are part of a complete collaboration ecosystem that offers high-quality, easy-to-use telepresence experiences that you have come to expect from Cisco, together with rapid global service and price-performance that make broad deployment easier and more affordable than ever. Whether you are just getting started with video communications or are planning to video-enable your entire organization, the MX300 G2 and MX200 G2 can meet your needs.

Features and Benefits

Table 1 lists the features and benefits of the Cisco TelePresence MX300 G2 and MX200 G2.

Table 1. Features and Benefits of Cisco TelePresence MX300 G2 and MX200 G2

Feature	Benefits
Design features	<ul style="list-style-type: none"> • Installs in minutes: The MX300 G2 and MX200 G2 are as easy to install as a TV, with a one-piece unit plus install configuration (floor stand, wheel base, and VESA wall mount. MX200 G2 also has a table-stand option). • Setup is simple: The MX300 G2 self-configures with Cisco® Unified Communications Manager (UCM), Cisco TelePresence Video Communication Server (VCS), or Cisco WebEx® Telepresence provisioning. Just authenticate your endpoint to the network to complete the setup. • Offers flexible camera features: Cisco TelePresence PrecisionHD Camera with pan, tilt, and zoom helps ensure optimal framing and video clarity. Its dedicated presets provide flexibility and easy viewing for any type of meeting. • Provides touch control: The 10-inch Cisco TelePresence Touch 10 interface offers simple, intuitive control. Easy “one-button-to-push” (OBTP) calling integrates with common calendaring programs. • Offers crisp, clear video: High-quality 55-inch or 42-inch displays deliver video resolutions of up to 1080p60 to let you bring the Cisco TelePresence experience to any team meeting room or corner office. • Provides high-fidelity stereo sound: Front speakers provide superior, optimized audio, and receive spatial audio from a Cisco TelePresence Server. • Allows you to meet with anyone, anywhere: The standards-based MX300 G2 and MX200 G2 lets you collaborate with anyone regardless of system - from PC video to immersive telepresence, to a meeting room around the globe. • Offers ability to connect and share: Collaborate naturally with 1080p content sharing with a touch of your finger. • Works the way you want: Search for your contacts in directories; create and store your own favorites; or manually dial out to other Cisco Unified Communications devices. You can connect through the network or through firewalls to any device (video or voice) or protocol.

Feature	Benefits
Application features	<ul style="list-style-type: none"> • Share multimedia and presentations at the touch of a button. • Supports Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs². • Supports Switched Conferencing (SVC) for enhanced layouts and enabling video on both screens of dual screen endpoints². • Easily control room peripherals such as lights, room dividers, curtains, directly from the Cisco TelePresence Touch 10 through customizable API³ (requires external third-party control system processor). • The dual-display feature allows another screen to be added for content sharing. • High-definition content sharing up to 1080p30 resolution is possible. • You can start a meeting with the OBTP feature.
Performance features	<ul style="list-style-type: none"> • The systems offers optimal definition up to 1080p60. • You can make H.323/Session Initiation Protocol (SIP) calls up to 6 Mbps. • Built-in individually transcoded multipoint conferencing lets you add three additional participants. • Provisioning and self-configuration are easy with Cisco UCM, Cisco TelePresence VCS, or Cisco WebEx Telepresence. • The MX300 G2 and MX200 G2 take advantage of the Cisco TelePresence Total Solution approach, including Cisco TelePresence recording and streaming, and firewall traversal services. • The systems are natively supported by Cisco UCM Version 8.6 or later.

Product Specifications

Table 2 lists the product specifications; Table 3 gives video and audio specifications; Table 4 gives network, security, and management specifications; and Table 5 gives ordering information for the Cisco TelePresence MX300 G2 and MX200 G2.

Table 2. Product Specifications

Product compatibility	Fully compatible with standards-compliant telepresence and video systems	
Software compatibility	Cisco TelePresence MX300 G2 Cisco TelePresence Software Version TC 7.0 or later Cisco Collaboration Endpoint Software Version 8.0 or later	Cisco TelePresence MX200 G2 Cisco TelePresence Software Version TC 7.2 or later Cisco Collaboration Endpoint Software Version 8.0 or later
Components	Fully integrated unit including: <ul style="list-style-type: none"> • Codec • Display • Camera • Integrated microphone and loudspeakers Cisco TelePresence Table Microphone 20 (two microphones are shipped with the MX300 G2, and one with the MX200 G2) Cables including DVI-I-to-VGA cable, 3.5-mm jack audio cable, LAN cable, and power cable	
Display	Cisco TelePresence MX300 G2: <ul style="list-style-type: none"> • 55-in. (1.4m) LCD monitor, edge LED backlight • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 4000:1 • Viewing angle: +/-178 deg • Response time: Typical 8 ms • Brightness: Typical 450 cd/m2 	Cisco TelePresence MX200 G2 <ul style="list-style-type: none"> • 42-inch LCD monitor, edge LED backlight • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 1300 • Viewing angle: +/- 178 deg • Response time: Typical 8 ms • Brightness: 450 cd/m2
PC and second-source video input	<ul style="list-style-type: none"> • DVI-I • Two HDMI 	
Supported PC input resolutions	SVGA (800 x 600) to 1080p (1920 x 1080)	

Camera overview	Cisco TelePresence MX300 G2: <ul style="list-style-type: none"> • 4x optical zoom (8x with digital) • Motorized +15°/-25° tilt, +/-90° pan • 72° horizontal field of view • 43.5° vertical field of view • Resolutions: 1080p60 and 720p60 • F 1.7 	Cisco TelePresence MX200 G2: <ul style="list-style-type: none"> • 2.5x optical zoom (5x with digital) • Motorized +5°/-25° tilt, +/- 30° pan • 83° horizontal field of view • 51.5° vertical field of view • Resolutions: 1080p60 and 720p60 • F 2.0
	<ul style="list-style-type: none"> • Automatic or manual focus, brightness, and white balance • Far-end camera control • Focus distance 0.98 ft (0.3m) to infinity 	
Audio system	<ul style="list-style-type: none"> • Integrated full-range and bass speakers • Integrated full-range microphone • Support for two Cisco TelePresence Table Microphone 20 microphones • Mini jack PC audio input • Mini jack audio output 	
User interface	Cisco TelePresence Touch 10 interface <ul style="list-style-type: none"> • 10-inch projected capacitive touch screen • Resolution: 1280 x 800 	
Language support	English, Arabic, Catalan, Czech, Danish, Dutch, Finnish, French, German, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazilian, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, and Turkish; depends on software version	
Physical dimensions (H x W x D)	Cisco TelePresence MX300 G2 main unit with: <ul style="list-style-type: none"> • Floor stand: 59.8 x 50.3 x 26.4 in. (1518 x 1278 x 671 mm) • Wall mount: 37.3 x 50.3 x 7.9 in. (948 x 1278 x 200 mm) • Wheel base: 63.2 x 50.3 x 29.7 in. (1605 x 1278 x 755 mm) 	Cisco TelePresence MX200 G2 main unit with: <ul style="list-style-type: none"> • Floor stand: 55 x 39.2 x 23.7 in. (1397 x 995 x 602 mm) • Table stand: 30.7 x 39.2 x 10.2 in. (781 x 995 x 259 mm) • Wall-mount: 26.4 x 39.2 x 5.7 in. (671 x 995 x 146 mm) • Wheel base: 58.3 x 995 x 711 in. (1480 x 39.2 x 28 mm)
Weight	Cisco TelePresence MX300 G2 main unit with (all weight without packaging): <ul style="list-style-type: none"> • Floor stand: 108.7 lb (49.3 kg) • Wall mount: 84.9 lb (38.5 kg) • Wheel base: 96.1 lb (43.6 kg) • Main unit only: 77.2 lb (35 kg) 	Cisco TelePresence MX200 G2 main unit with (all weight without packaging): <ul style="list-style-type: none"> • Floor stand: 108.7 lb (36.3 kg) • Table stand: 56.2 lb (25.5 kg) • Wall mount: 56.2 lb (25.5 kg) • Wheel base: 73 lb (33.1kg) • Main unit only: 52.9 lb (24 kg)
Physical dimensions and weight of packaging (H x W x D)	Cisco TelePresence MX300 G2: Consolidated package size: 48.9 x 57.9 x 25 in. (1241 x 1470 x 635 mm) Shipping weight with: <ul style="list-style-type: none"> • Floor stand: 200.6 lb (91.2 kg) • Wall mount: 176.4 lb (80.0 kg) • Wheel base: 180.8 lb (82.8 kg) 	Cisco TelePresence MX200 G2: Consolidated package size: 42.6 x 53.5 x 28.2 in. (1081 x 1360 x 716 mm) Shipping weight with: <ul style="list-style-type: none"> • Floor stand: 149.9 lb (68.0 kg) • Wall mount: 127.9 lb (58.2 kg) • Wheel base: 143.3 lb (65.4 kg) • Table stand: 134.5 lb (61.2 kg)
Power	Autosensing power supply 100-240 VAC, 50-60 Hz Rated: 300W maximum Power consumption: 235W at maximum standardized configuration	

Temperature range	<p>Operating temperature and humidity:</p> <ul style="list-style-type: none"> • Ambient temperature: 32 to 95°F (0 to 35°C) • Relative humidity (RH): 10 to 90% • Storage and transport temperature at RH 10-90% (noncondensing): -4 to 140°F (-20 to 60°C)
Approvals and compliance	<ul style="list-style-type: none"> • Directive 2006/95/EC (Low-Voltage Directive) - Standard EN 60950-1 • Directive 2004/108/EC (EMC Directive) - Standard EN 55022, Class A - Standard EN 55024 - Standard EN 61000-3-2/-3-3 • Directive 2011/65/EU (RoHS) • Approved according to UL 60950-1 and CNA/CSA C22.2 No. 60950-1-07 • Compliance with FCC15B Class A

Table 3. Video and Audio Specifications

Bandwidth	H.323 and SIP up to 6 Mbps point-to-point
Minimum bandwidth for resolution and frame rate	<ul style="list-style-type: none"> • 720p30 from 768 kbps • 720p60 from 1152 kbps • 1080p30 from 1472 kbps • 1080p60 from 2560 kbps
Video standards	<ul style="list-style-type: none"> • H.263 • H.263+ • H.264
Video features	<ul style="list-style-type: none"> • Advanced screen layouts • Local auto-layout
Video inputs (three inputs)	<p>Two HDMI and one DVI-I (analog and digital) inputs</p> <p>Supports formats up to maximum 1920 x 1080 @ 60 fps (HD1080p60), including:</p> <ul style="list-style-type: none"> • 640 x 480 • 720 x 480 • 720 x 576 • 800 x 600 • 848 x 480 • 1024 x 768 • 1152 x 864 • 1280 x 720 • 1280 x 1024 • 1280 x 768 • 1280 x 800 • 1280 x 960 • 1360 x 768 • 1366 x 768 • 1400 x 1050 • 1440 x 900 • 1680 x 1050 • 1920 x 1080 <p>High-definition inputs use progressive video formats</p> <p>Extended Display Identification Data (EDID)</p>
Video outputs (one output)	<p>One HDMI output</p> <p>Supports formats up to maximum 1920 x 1080 @ 60 fps (HD1080p60), including:</p> <ul style="list-style-type: none"> • 1920 x 1080 @ 60 fps (1080p60) • 1920 x 1080 @ 50 fps (1080p50) • 1280 x 720 @ 60 fps (720p60) • 1280 x 720 @ 50 fps (720p50) • 1366 x 768 @ 60 fps (WXGA) • 1360 x 768 @ 60 fps (WXGA) • 1280 x 768 @ 60 fps (WXGA) <p>VESA Monitor Power Management</p> <p>EDID</p>

Live video resolutions (encode/decode)	<p>Supports encode/decode video formats up to maximum 1920 x 1080@60 fps (HD1080p60), including:</p> <ul style="list-style-type: none"> • 176 x 144 @ 30 fps (QCIF) (decode only) • 352 x 288 @ 30 fps (CIF) • 512 x 288 @ 30 fps (w288p) • 576 x 448 @ 30 fps (448p) • 768 x 448 @ 30 fps (w448p) • 704 x 576 @ 30 fps (4CIF) • 1024 x 576 @ 30 fps (w576p) • 640 x 480 @ 30 fps (VGA) • 800 x 600 @ 30 fps (SVGA) • 1024 x 768 @ 30 fps (XGA) • 1280 x 1024 @ 30 fps (SXGA) • 1280 x 720 @ 30 fps (720p30) 	<ul style="list-style-type: none"> • 1280 x 768 @ 30 fps (WXGA) • 1920 x 1080 @ 30 fps (1080p30) • 1440 x 900 @ 30 fps (WXGA+) • 1680 x 1050 @ 30 fps (WSXGA+) • 512 x 288 @ 60 fps (w288p60) • 768 x 448 @ 60 fps (w448p60) • 1024 x 576 @ 60 fps (w576p60) • 1280 x 720 @ 60 fps (720p60)
Audio standards	<ul style="list-style-type: none"> • 64- and 128-kbps AAC-LD • G.722 • G.722.1 • G.711 • G.729 AB • OPUS 	
Audio features	<ul style="list-style-type: none"> • High-quality 20 kHz stereo audio • Three acoustic echo cancellers • Automatic Gain Control (AGC) • Automatic noise reduction • Active lip synchronization 	
Dual stream	<ul style="list-style-type: none"> • H.239 (H.323) dual stream • Binary Floor Control Protocol (BFCP) (SIP) dual stream • Supports resolutions up to 1080p (1920 x 1080) 	
Multipoint support	<ul style="list-style-type: none"> • Four-way embedded SIP/H.323 Multipoint (reference MultiSite) • Adhoc conferencing • Switched Conferencing (SVC)² 	
MultiSite features (embedded multipoint)	<ul style="list-style-type: none"> • Adaptive SIP/H.323 MultiSite • Three-way resolution up to 720p30 • Four-way resolution up to 576p30 • Full individual audio and video transcoding • Individual layouts in MultiSite continuous presence • H.323/SIP and voice over IP (VoIP) in the same conference • Support for presentation (H.239 and BFCP) from any participant at resolutions up to 1080p30/SXGA • Best impression (automatic continuous presence layouts) • H.264, encryption, and dual stream from any site • IP Downspeeding • Dial in and dial out • Conference rates up to 6 Mbps 	

Table 4. Network, Security, and Management Specifications

Protocols	<ul style="list-style-type: none"> • H.323 • SIP
Network interfaces	<ul style="list-style-type: none"> • One Ethernet (RJ-45) auto-sensing Gigabit (10/100/1000) LAN port • One Fast Ethernet (10/100) PoE port for Touch 10
Other interfaces	<ul style="list-style-type: none"> • Micro USB for service

IP network features	<ul style="list-style-type: none"> • Domain Name System (DNS) lookup for service configuration • Differentiated Services (quality of service [QoS]) • IP adaptive bandwidth management (including flow control) • Auto-gatekeeper discovery • Dynamic playout and lip-sync buffering • H.245 dual-tone multifrequency (DTMF) tones in H.323 • Date and time support with Network Time Protocol (NTP) • Packet-loss-based downspeeding • DNS-based Uniform Resource Identifier (URI) dialing • TCP/IP • Dynamic Host Configuration Protocol (DHCP) • IEEE 802.1x network authentication • IEEE 802.1q VLAN • IEEE 802.1p (QoS and class of service [CoS]) • Cisco ClearPath
IPv6 network support	<ul style="list-style-type: none"> • Dual stack (IPv4 and IPv6) for H.323 and SIP • Dual stack (IPv4 and IPv6) for DHCP, SSH, HTTP, HTTPS, DNS, and DiffServ • Support for static IP address assignment, stateless autoconfiguration, and DHCPv6
Firewall traversal	<ul style="list-style-type: none"> • Cisco TelePresence Expressway technology • H.460.18 and H.460.19 Firewall Traversal • SIP ICE (Interactive Connectivity Establishment)
Embedded encryption	<ul style="list-style-type: none"> • H.323 and SIP point-to-point • Standards-based: H.235v3 and Advanced Encryption Standard (AES) • Automatic key generation and exchange • Support in dual stream
Security features	<ul style="list-style-type: none"> • Management through Secure HTTP (HTTPS) and Secure Shell (SSH) Protocol • IP administration password • Password protected Administration menu • Disable IP services • Network settings protection
System management	<ul style="list-style-type: none"> • Support for the Cisco TelePresence Management Suite (TMS) • Total management through embedded Simple Network Management Protocol (SNMP), Telnet, SSH, XML, and Simple Object Access Protocol (SOAP) • Remote software upload: Through web server, HTTP, and HTTPS
Directory services	<ul style="list-style-type: none"> • Support for local directories (My Contacts) • Corporate directory (through Cisco UCM and Cisco TMS) • Server directory supporting LDAP and H.350 (requires Cisco TelePresence Management Suite) • Call History with received, placed, and missed calls with date and time

¹ Requires Collaboration Endpoint Software 8.2 or later

² Requires Collaboration Endpoint Software 8.0 or later

³ Requires Collaboration Endpoint Software 8.1 or later

Ordering Information

To place an order, please contact your local Cisco representative and refer to Table 5.

Table 5. Ordering Information

Product Name	Part Number	Compliance Model Number
Cisco TelePresence MX300 G2	CTS-MX300-K9	TTC60-19
MX300 G2 MultiSite Option	LIC-MX300-MS	
Cisco TelePresence MX200 G2	CTS-MX200-K9	TTC60-20
MX200 G2 MultiSite Option	LIC-MX200-MS	

Cisco Service and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, please visit:

<http://www.cisco.com/go/telepresenceservices>.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more](#).

For More Information

For more information about the Cisco TelePresence MX Series, visit <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)